



# LED RETROFIT UNITS ROUND 4, 5 & 6"



4"  
**G-48332**



4"  
**G-19765 G-83447-30K**  
**G-19767 G-83447-50K**



5&6"  
**G-83448-30K**  
**G-83448-50K**



5&6"  
**G-48333**



ITEM	G-48332	G-19765	G-83447-30K	G-19767	G-83447-50K
DESCRIPTION	R4/10W/R/LED/5CCT	R4/10W/R/LED/27k	R4/12W/R/LED/30k	R4/12W/R/LED/41k	R4/10W/R/LED/50k
COLOR TEMP	27, 30, 35, 41, 50k	2700k	3000k	4100k	5000k
OUTPUT LUMEN	850	750	850	850	750
BEAM ANGLE	100°	100°	100°	100°	100°
WATTAGE	10W	10W	12W	12W	10W
EQUIV. WATTAGE	75W	65W	75W	75W	65W
CRI	>90	>90	>90	>90	>90
DIMMABLE	Yes	Yes	Yes	Yes	Yes
PACK	12	24	24	24	24
OD	5.35	5.40	5.40	5.40	5.40
HEIGHT	2.84	2.80	1.70	1.70	2.80
ENVIRONMENT	Wet location	Damp location	Damp location	Damp location	Damp location

ITEM	G-83448-30K	G-83448-50K	G-48333 <small>Wall Switch Technology</small>
DESCRIPTION	R5-6/18W/R/LED/30k	R5-6/18W/R/LED/50k	R5-6/16W/R/LED/3CCT
COLOR TEMP	3000K	5000K	30, 41, 50K
OUTPUT LUMEN	1250	1250	1250
BEAM ANGLE	100°	100°	100°
WATTAGE	18W	18W	16W
EQUIV. WATTAGE	120W	120W	120W
CRI	>90	>90	>90
DIMMABLE	Yes	Yes	Yes
PACK	16	16	16
OD	7.25	7.25	7.48
HEIGHT	3.46	3.46	3.40
ENVIRONMENT	Damp location	Damp location	Wet Location

## Accessories

### Emergency Led Driver

15W G-48410 30W G-48411



Dimmable:  
5%



Lifetime:  
50,000 hours



Warranty:  
1 year



## 120V Dimmer List

BRAND	MODEL	DIMMING RATE
Cooper	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%

BRAND	MODEL	DIMMING RATE
Lutron	DV-600PR / DV603PG	10 - 100%
	DVW-603PGH / DVCL-153P	10 - 100%
	MACL-153M / TGCL-153P	10 - 100%
	S-600PR / S-2-LH	10 - 100%