

24V 90 WATTS 2835 LED TAPE LIGHT DIMMABLE



G-48495



SOFT WHITE
2700K

G-48498



COOL WHITE
4100K

G-48496



WARM WHITE
3000K

G-48499



SUPER WHITE
5000K

G-48497



NEUTRAL WHITE
3500K

ITEM	G-48495	G-48496	G-48497	G-48498	G-48499
DESCRIPTION	T160/2835/18W/27K	T160/2835/18W/30K	T160/2835/18W/35K	T160/2835/18W/41K	T160/2835/18W/50K
VOLTAGE	24V DC	24V DC	24V DC	24V DC	24V DC
WATTS	5.48 FT / 18W M	5.48 FT / 18W M	5.48 FT / 18W M	5.48 FT / 18W M	5.48 FT / 18W M
LUMENS	883 Ft / 2900 M	892 Ft / 2928 M	913 Ft / 2998 M	919 Ft / 3016 M	925 Ft / 3038 M
BEAM ANGLE	120°	120°	120°	120°	120°
DIMMABLE	5%	5%	5%	5%	5%
LED QUANTITY	160	160	160	160	160
WIDTH	10 mm	10 mm	10 mm	10 mm	10 mm
HEIGHT	1.85 mm	1.85 mm	1.85 mm	1.85 mm	1.85 mm
CUTTABLE	2.18"	2.18"	2.18"	2.18"	2.18"
COLOR TEMPERATURE	Soft White 2700k	Warm White 3000k	Neutral White 3500k	Cool White 4100k	Super White 5000k
CRI	94>	94>	94>	94>	94>
ADHESIVE	3M 9495 300 MP	3M 9495 300 MP	3M 9495 300 MP	3M 9495 300 MP	3M 9495 300 MP
ROLL LENGTH	16.4 FT / 5 M	16.4 FT / 5 M	16.4 FT / 5 M	16.4 FT / 5 M	16.4 FT / 5 M

High Density tape low pixels smooth and uniform beam. light features highly efficient and compact LED chip sets that allow for tighter spacing without sacrificing lumen loss

- Low heat generation, Channel not required for heat sink
- Double end impute power connection option
- Ultra-high lumen output capability
- 90+ color rendering index
- Available in 2700K, 3000K, 3500K, 4000K, and 5000K
- 50,000 hours rated life



Warranty:
3 years



Dimmable:
5%



Inner/Master
25/100



Double end
Connector

