

5" & 6"
G-483335" & 6"
G-483395" & 6"
G-83448-30K
G-83448-50K

ITEM	G-48333 Wall Switch Technology	G-48339	G-83448-30K	G-83448-50K
DESCRIPTION	R5-6/16W/R/LED/3CCT	R5-6/14W/R/LED/5CCT	R5-6/18W/R/LED/30k	R5-6/18W/R/LED/50k
COLOR TEMP	30, 41, 50K	27, 30, 35, 41, 50k	3000K	5000k
OUTPUT LUMEN	1250	1350	1250	1250
BEAM ANGLE	100°	100°	100°	100°
WATTAGE	16W	14W	18W	18W
EQUIV. WATTAGE	120W	120W	120W	120W
CRI	>90	>90	>90	>90
DIMMABLE	Yes	Yes	Yes	Yes
PACK	16	6	16	16
OD	7.48	7.25	7.25	7.25
HEIGHT	3.40	3.15	3.46	3.46
ENVIRONMENT	Wet location	Wet location	Damp location	Damp location

120V Dimmer List

BRAND	MODEL	DIMMING RATE	BRAND	MODEL	DIMMING RATE
Cooper	DLC03P	10 - 100%	Lutron	DV-600PR / DV603PG	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%		DVW-603PGH / DVCL-153P	10 - 100%
	6631 / 6633	10 - 100%		MACL-153M / TGCL-153P	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%		S-600PR / S-2-LH	10 - 100%

Accessories

Emergency Led Driver

15W G-48410 30W G-48411

